



## aart 8 [CodeNr. 10201]

The aart 8 is a two-way high-performance, multipurpose loudspeaker system designed for professional portable and installed applications. With a 100°H x 50°V coverage pattern it combines high output capability with excellent sound performance in a trapezoidal compact enclosure, made of 15 mm plywood.

It features a powerful 8" speaker for MF/LF frequency range, and a 1" (25mm) exit HF compression driver for extended high frequency response. An advanced passive crossover, with PTC driver protection, matches the components working perfectly together and allows full-range application without additional electronics.

The versatile aart 8 suits for speech and music applications as a stand-alone fullrange loudspeaker or MF/HF speaker in sound reinforcement systems.

### Key features

- > 1" exit HF compression driver
- > Compact design
- > User-rotatable, 100° x 50° horn
- > Passive fullrange operation
- > Vertical and horizontal orientation
- > Crossover with HF protection
- > Pole mount flange
- > M6 inserts for flexible mounting options
- > Weight only 8,5 kg

### Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Nightclubs
- > Corporate AV events and conferences

### Recommended with

- > Subs:  
aart sat Bass
- > Amps:  
QX 4/800

For more informations please check our webside or contact us.

### Specification

Loudspeaker Type	Fullrange, two-way, passive
Frequency Range (-10dB)	70 Hz - 20 kHz
Frequency Response (± 3dB)	80 Hz - 17,5 kHz
Coverage Pattern	H 100° x V50° nominal (user-rotatable)
Power Handling	200W continuous, 800 W peak
System Sensitivity (1w/1m)	95 dB
Maximum SPL (calc. 1m)	118 dB continuous, 124 dB peak
HF Driver	1,35"voice coil, 1" exit compression driver
LF Driver	8" speaker aaCRAAFT
Nominal Impedance	4 ohms
Crossover	2,7 kHz passive
Protection	PTC driver protection
Enclosure	Birch plywood
Finish	Black textured paint
Fittings	5x M6 inserts, 1x bar handle, pole-mount socket
Protective Grille	Black perforated steel with acoustic transparent foam backing
Connectors	1x NL4, Pins 1+/1-
Dimensions mm (WxHxD)	220 x 440 x 250
Weight (kg)	8,5 kg

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax:+49 (0) 85 31 / 97 85 07 | Email: info@solton-acoustic.de | Web: www.solton.de