



CX 215 Sub [CodeNr. 12102]

The Solton CX 215 Sub is a dual 15" direct-radiating high performance subwoofer system. It has been designed to add high-output, high-impact bass response to the mid-high and fullrange loudspeaker systems in various mobile and installed applications. It can be used as the low frequency section of a bi-amped or tri-amped systems.

The CX 215 Sub features two long-excursion, 15" ,4" (100mm) voice coil aaCraaft drivers and a low distortion port design.

The CX 215 Sub has many features that make it a versatile subwoofer system

Key features

- > Dual long-excursion, 15" ,4" (100mm) voice coil LF Transducer
- > 137 dB Peak SPL
- > Active / Passive operation (switchable)
- > Pole mount socket x 2 (M20)
- > Four Integrated Handles for Easy Portability
- > Prepared for 100mm blue wheels

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Nightclubs

Recommended with

- > Tops:
CX 212, CX 15 Hi+, CL 6, AS 88/2 N, AS 12/2, HD 151, RB82, HD 88
- > Amps:
DX 48, DX 4
- > Controller:
DSP 206 N

For more informations please check our webside or contact us.

Specification

Loudspeaker Type	Double 15"; bass-reflex, subwoofer
Frequency Range (- 10dB)	35 Hz - 200 Hz
Frequency Response (\pm 3dB)	45 Hz – 150 Hz
Coverage Pattern	Omni
Power Handling	1200 W continuous, 2400 W max.
System Sensitivity (1w/1m)	100 dB
Maximum SPL (Calculated at 1m)	131 dB continuous, 137 dB peak
HF Driver	n/a
LF Driver	2 x15"; 4" voice coil speaker aaCRAAFT
Nominal Impedance	4 ohms
Crossover	Active / Passive switchable, 125 Hz
Protection	n/a
Active Tunings / Features	n/a
Enclosure	15mm birch plywood
Finish	Black textured paint
Fittings	2 x Handles per side, 2x M20 pole
Protective Grille	Black perforated steel with acoustic transparent foam
Connectors	2 x NL4
Dimensions mm (WxHxD)	600 x 1000 x 690
Weight	68 kg

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax:+49 (0) 85 31 / 97 85 07 | Email: info@solton-acoustic.de | Web: www.solton.de