



CL 15 Flyable Sub [CodeNr. 12003]

The Solton CL 15 Sub is a single 15" direct-radiating high performance subwoofer system.

It has been designed to add high-output, high-impact bass response to the mid-high and fullrange loudspeaker systems in various mobile and installed applications.

The CL 15 Sub features a long-excursion, 15" ,3" (100mm) voice coil LF transducer, and a low distortion port design in a compact reflex enclosure made of 15 mm birch plywood.

The CL 15 Sub must be electronically crossed over with the Solton DSP 206N or equivalent Electronic Controller.

The integrated flyware enable the flown operation together with CL 6 line array.

The CL 15 Sub has features that make it a interesting subwoofer system for several special applications.

Key features

- > 1 x 15" , 3" (100mm) voice coil LF Transducer
- > High output
- > Integrated flying hardware
- > Compact design
- > Two Integrated Handles for Easy Portability

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Nightclubs

Recommended with

- > Tops:
CL 6
- > Amps:
QX 2400, DX4
- > Controller:
DSP 206 N

Additional

Art. Nr. 12518 (FLC 6-15)
Flying frame for CL 6 and CL 15 Sub

For more informations please check our website or contact us.

Specification

Loudspeaker Type	Single15", bass-reflex, subwoofer, flyable
Frequency Range (-10dB)	35 Hz -250 Hz
Frequency Response (\pm 3dB)	40 Hz -200 Hz
Coverage Pattern	Omni
Power Handling	600 W continuous, 2400 W peak
System Sensitivity (1w/1m)	98 dB
Maximum SPL (Calculated at 1m)	126 dB continuous, 132 dB peak
HF Driver	n/a
LF Driver	15", 3" voice coil speaker
Nominal Impedance	8 ohms
Crossover	Active
Protection	n/a
Active Tunings / Features	n/a
Enclosure	15 mm birch plywood
Finish	Black textured paint
Fittings	2 x Handles, Rigging system
Protective Grille	Black perforated steel with acoustic transparent foam
Connectors	2 x NL 4
Dimensions mm (WxHxD)	650 x 460 x 530
Weight	31 kg

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax:+49 (0) 85 31 / 97 85 07 | Email: info@solton-acoustic.de | Web: www.solton.de