



## CT 5 [CodeNr. 10901]

The CT-5 is a 4 x 5"/ 2-way premium vertical array loudspeaker system in a very compact and discreet design.

With a 120° H x 15° V coverage pattern it combines very high output capability with excellent sound performance. It features four powerful 5" speakers for LF/MF frequency range, and one ribbon driver for extended high frequency response. The power rating of the CT-5 is 320 W (RMS), the impedance is 4 ohms.

The low-profile CT-5 loudspeaker is very flexible and suitable for permanent installations as well as MF/HF speaker in sound systems

Also available in white. [CodeNr. 11904]

### Specification

Loudspeaker Type	4 x 5", two-way, compact line array
Frequency Range (-10dB)	90 Hz - 20 kHz
Frequency Response (± 3dB)	100 Hz - 18 kHz
Coverage Pattern	H 120° x V 15° nominal (user-rotatable)
Power Handling	320W continuous, 1280 W peak
System Sensitivity (1w/1m)	95 dB
Maximum SPL (Calculated at 1m)	123 dB continuous, 128 dB peak
HF Driver	Ribbon driver
LF Driver	4 x 5" woofer
Nominal Impedance	4 ohms
Crossover	2,5 kHz passive
Protection	PTC driver protection
Active Tunings / Features	n/a
Enclosure	Plywood
Finish	Black or White textured paint
Fittings	Pole-mount socket
Protective Grille	Black perforated steel with acoustic transparent
Connectors	1 x NL4
Dimensions mm (WxHxD)	160 x 860 x 120
Weight	8 kg

### Key features

- > High SPL with smooth response
- > Outstanding dynamic sound and excellent headroom
- > Dispersion 120° x 15° (HxV)
- > Attractive, elegant and discreet design
- > PTC driver protection
- > Weight only 8 kg

### Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Theater
- > Corporate AV events and conferences
- > Church

### Recommended with

- » Subs:  
TA-15 Sub, aart bass
- » Amps:  
QX 4/800
- » Controller  
DSP 206 N

For more informations please check our webside or contact us.

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax: +49 (0) 85 31 / 97 85 07 | Email: [info@solton-acoustic.de](mailto:info@solton-acoustic.de) | Web: [www.solton.de](http://www.solton.de)