



CT 5 N [CodeNr. 13307]

The CT-5N is a new 4 x 5" / 2-way premium vertical array loudspeaker system in a very compact and discreet design.

With a 120° H x 20° V coverage pattern it combines very high output capability with excellent sound performance. It features four powerful 5" speakers for LF/MF frequency range, and one neodym compression driver for extended high frequency response.

The power rating of the CT-5N is 320 W (RMS), the impedance is 4 ohms.

The low-profile CT-5N loudspeaker is very flexible and suitable for permanent installations as well as MF/HF speaker in sound systems.

Also available in white. [CodeNr. 13307]

Specification

Loudspeaker Type	4 x 5", two-way, compact line array
Frequency Range (-10dB)	90 Hz - 20 kHz
Frequency Response (± 3dB)	100 Hz - 18 kHz
Coverage Pattern	H 120° x V 20° nominal
Power Handling	320W continuous, 1280 W peak
System Sensitivity (1w/1m)	97 dB
Maximum SPL (Calculated at 1m)	122 dB continuous, 128 dB peak
HF Driver	1" Neodym HF compression driver
LF Driver	4 x 5" woofer
Nominal Impedance	4 ohms
Crossover	2,1 kHz passive
Protection	PTC driver protection
Active Tunings / Features	n/a
Enclosure	Birch Plywood
Finish	Black polyurea coating (white)
Fittings	8x M8 inserts, 1x handle Pole socket, U-bracket optional
Protective Grille	Black perforated steel with acoustic transparent
Connectors	1 x NL4 1+/1-
Dimensions mm (WxHxD)	150 x 880 x 124
Weight	8 kg

Key features

- > High SPL with smooth response
- > Outstanding dynamic sound and excellent headroom
- > Dispersion 120° x 20° (HxV)
- > Attractive, elegant and discreet design
- > PTC driver protection
- > Weight only 8 kg

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Theater
- > Corporate AV events and conferences
- > Church

Recommended with

- » Subs:
aart SUB 315
- » Amps:
QX 700, DX 43
- » Controller
DSP 206 N

For more informations please check our webside or contact us.