



CT 4 L [CodeNr. 10801]

The CT-4 L is a 4 x 4" / 2-way premium vertical array loudspeaker system in a very compact and discreet design.

With a 120°H x 15°V coverage pattern it combines very high output capability with excellent sound performance. It features four powerful 4" speakers for LF/MF frequency range, and one ribbon driver for extended high frequency response. The power rating of the CT-4 L is 280 W (RMS), the impedance is 4 ohms.

The low-profile CT-4 loudspeaker is very flexible and suitable for permanent installations as well as MF/HF speaker in sound systems.

Also available in white. [CodeNr. 11903]

Key features

- > High SPL with smooth response
- > Outstanding dynamic sound and excellent headroom
- > Dispersion 120° x 15° (HxV)
- > Attractive, elegant and discreet design
- > PTC driver protection
- > Weight only 5,5 kg

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Theater
- > Corporate AV events and conferences
- > Church

Recommended with

- » Subs:
TA-12 Sub, aart bass, Sub 315,
- » Amps:
QX 4/800
- » Controller
DSP 206 N

For more informations please check our website or contact us.

Specification

Loudspeaker Type	4 x 4", two-way, compact line array
Frequency Range (-10dB)	100 Hz - 20 kHz
Frequency Range (± 3dB)	120 Hz - 18 kHz
Coverage Pattern	H 120° x V 15° nominal
Power Handling	280 W continuous, 1120 W peak
System Sensitivity (1w/1m)	92 dB
Maximum SPL (Calculated at 1m)	116 dB continuous, 122 dB peak
HF Driver	Ribbon driver
LF Driver	4 x 4" woofer
Nominal Impedance	4 ohms
Crossover	2,5 kHz passive
Protection	PTC driver protection
Active Tunings / Features	n/a
Enclosure	Wood
Finish	Black textured paint Black or White
Fittings	pole-mount socket
Protective Grille	Black perforated steel with acoustic ransparent foam backing
Connectors	1 x NL4
Dimensions mm (WxHxD)	140 x 820 x 120
Weight	5,5 kg

Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking/Rottau | GERMANY | Phone: +49 (0) 85 31 / 91 38 80

Fax:+49 (0) 85 31 / 97 85 07 | Email: info@solton-acoustic.de | Web: www.solton.de